



KONICA MINOLTA



Rhopoint TAMS™ Total Appearance Measurement System



Next Generation Paint Quality Instrument:
Setting New Standards in Appearance Measurement

In cooperation with Volkswagen AG & AUDI AG

Giving Shape to Ideas

Measurements that closely correlate to human perception are easier to understand and communicate.

For maximum impact, an automotive paint finish must instantly produce an appealing visual sensation for the customer. This can only be achieved if the overall surface finish displays both high **QUALITY** and **HARMONY**.

Rhopoint TAMS is a new way of quantifying appearance quality inspired by a four-year collaboration between Rhopoint, Volkswagen AG and AUDI AG. This innovative new technology models the human perception of surface appearance quality, providing new parameters that revolutionise the understanding and communication of visual appearance information.

Improved correlation and easy communication gives Rhopoint TAMS a major advantage over existing methods that produce complex results relying on the user to interpret the values into a real-life visual experience.

Rhopoint TAMS technology provides opportunities to **improve surface finish**, establish **improved quality criteria** and **remove subjectivity in visual assessment**.

DEFINES



QUALITY

One single value rates the total appearance quality of a surface. 100% indicates a smooth finish with perfect image forming characteristics. Rhopoint TAMS quality is calculated using waviness and sharpness values predicting the visual rating of the customer.



HARMONY

Based on extensive human perception research by AUDI AG, this value indicates the acceptability of adjacent car parts. It is calculated using Waviness and Dimension parameters. A value of >1.0 indicates parts are not similar and if viewed together will detract from overall visual quality.



PERCEPTION

Data from the Rhopoint TAMS vision system is processed using perception algorithms derived from extensive human perception studies.



CONTRAST

Contrast is related to the color of the surface; white and metallic surfaces have low contrast, a deep black measures 100%. Contrast quantifies the visual impact of orange peel and haze effects both being more visible on high contrast dark colors.



Reflection in a White surface
C= 40%



Reflection in a Black surface
C= 100%




SHARPNESS

Sharpness quantifies the accuracy of images reflected in the surface, 100% indicates a perfect reflection.


At close distances (<0.5m) sharpness measures how well surface reflects fine details. At showroom viewing distance (1.5m) sharpness quantifies haze and clarity.

Close Distance view of an unsharp surface:




S= 65%

Close Distance view of a sharp surface:




S= 98%

Showroom Distance view of an unsharp surface:



Showroom Distance view of a sharp surface:






WAVINESS

Correlated to human perception, waviness quantifies the visible impact of surface waves to an observer at showroom distance (1.5m). The waviness of a surface is critical for determining appearance quality. Low waviness surfaces tend to be preferred by the viewer.


Flat surface:



Wavy surface:




Small structure dominant surface:



DIMENSION


Indicates the dominant structure size perceived at showroom viewing distance. Typical values are between 1 – 6mm, the dominant structure size is important in determining the harmony between adjacent panels/parts.

Large structure dominant surface:




TAMS™ VISION


To achieve close correlation with human perception Rhopoint TAMS emulates the human evaluation of a reflective surface, changing its imaging system focus from surface to reflected image.



The image transfer qualities of the surface are measured and used to calculate sharpness and contrast.



Waviness is calculated by quantifying distortion in a reflected image.



Surface topography is analysed to identify the Dominant structure.





APPLICATION OPTIONS





Rhopoint TAMS is able to capture surface data for mid gloss and high gloss surfaces offering the possibility of measuring all surfaces throughout the automotive manufacturing process - steel and aluminium, E-Coat as well as filler, base coat and top coat.

TAMS™ CONCEPT

- 1 Operation Touch-screen
- 2 Camera sensor
- 3 Target screen
- 4 Focus system and actuator
- 5 Dual Processor: 1 GHz ARM Cortex A8 + DSP
- 6 RFID module
- 7 Removeable/rechargeable batteries
- 8 Push & Start pressure sensitive auto-measure system



-  Dual focus camera operation captures **all** surface appearance data
-  **Fast** operation with powerful on board image processing
-  Easy to use with on screen menu navigation prompts
-  **Safe** to use- static measurement with soft contact area

-  **Ergonomic** operation-measure entire vehicle more easily
-  **Fast & Easy** data transfer via SD card
-  Flexible power options - 2x removable rechargeable battery or mains operation
-  **RFID** Enhanced process integration via RFID

Specifications Rhopoint TAMS™

SHARPNESS	
Units	S (%)
Minimum (No visible reflection)	0
Maximum (Perfect mirror)	100
Resolution	0.1
Repeatability	0.1 (SD)
Reproducibility	0.5 (SD)
Measurement Technique	Optical Transfer Function

WAVINESS	
Units	W (W units)
Minimum	0
Maximum (typical)	30
Resolution	0.1
Repeatability	0.2 (SD)
Reproducibility	1 (SD)
Measurement Technique	Reflected Image Line Deformation Analysis
Correlation	AUDI AG MDS Perception analysis

QUALITY	
Units	Q (%)
Minimum	0
Maximum (typical)	100
Resolution	0.1
Repeatability	0.2 (SD)
Reproducibility	0.8 (SD)
Algorithm	Calculated using Sharpness & Waviness
Correlation	Volkswagen AG Quality Perception Studies

INSTRUMENT SPECIFICATION	
Menu Interface	5 Capacitive Sense buttons
Measurement Operation	Tactile button, capacitive sensor, push & start auto measurement system
Measurement Time	4 Second Image Capture 4 Second Processing
Color Screen	Full color IPS screen
Power	Removeable and rechargeable lithium polymer batteries
Operation	Up to 5 hours/charge
Memory	>10,000 readings 8GB internal / 8GB SD card
Data Transfer	SD Card, USB, Ethernet

CONTRAST	
Units	C (%)
Minimum (Perfect Diffuse White)	0
Maximum (Perfect Black)	100
Resolution	0.1
Repeatability	0.1 (SD)
Reproducibility	0.3 (SD)
Measurement Technique	Optical Transfer Function

DIMENSION	
Units	D (mm)
Minimum	0.5
Maximum (typical)	8
Resolution	0.1
Repeatability	0.1 (SD)
Reproducibility	0.4 (SD)
Measurement Technique	Phase Measurement Deflectometry
Correlation	AUDI AG MDS Perception analysis

HARMONY	
Units	H (H units)
Minimum	0
Maximum (typical)	8.9
Resolution	0.1
Repeatability	0.1 (SD)
Reproducibility	0.2 (SD)
Algorithm	Calculated using Waviness & Dimension
Correlation	AUDI AG MDS Perception analysis

Optical System	Variable Focus Machine Vision
Spatial Resolution (surface)	34µm/pixel
Field of View (surface)	25 x 16 mm
Processor Specification	ARM A8 Dual core + Digital Signal Processor
Production Integration	RFID TAG Reader (optional)
Dimensions / Weight	172 x 136 x 56 mm / 950g
Additional Sensors	Accelerometer, Orientation, 4 x Pressure (measurement)
Construction	Aluminium instrument case

ACCESSORIES (INCLUDED)

Instrument, Carry Case, 2 x removable & rechargeable batteries, calibration plate, AC Adapter, certificate, cleaning cloth, spare measurement baffle

Konica Minolta Sensing Europe B.V. is an authorized Distributor of Rhopoint Instruments Ltd.

KONICA MINOLTA, INC
Konica Minolta Sensing Americas, Inc.

Osaka, Japan
New Jersey, U.S.A.

Konica Minolta Sensing Europe B.V.

European Headquarter
German Office
French Office
UK Office
Italian Office
Swiss Office
Polish Office
Turkish Office
Belgium Office
Nordic Office
SE Sales Division
Beijing Office
Guangzhou Office
Chongqing Office
Qingdao Office
Wuhan Office

Konica Minolta (CHINA) Investment Ltd.

Konica Minolta Sensing Singapore Pte Ltd.
Konica Minolta Sensing, Inc.

Optics Company, Korea
Optics Company, Sensing Business
Thailand Representative Office

Nieuwegein, Netherlands
München, Germany
Roissy CDG, France
Warrington, United Kingdom
Cinisello Balsamo, Italy
Dietikon, Switzerland
Wrocław, Poland
Istanbul, Turkey
Zaventem, Belgium
Västra Frölunda, Sweden
Shanghai, China
Beijing, China
Guangzhou, China
Chongqing, China
Shandong, China
Hubei, China
Singapore
Goyang-si, Korea
Bangkok, Thailand

Phone: +1-888-473-2656 (in USA)
Phone: +1-201-236-4300 (outside USA)

Phone: +31 (0) 30 248-1193
Phone: +49 (0) 89 4357 156 0
Phone: +33 (0) 1 80-11 10 70
Phone: +44 (0) 1925 467300
Phone: +39 02 84948800
Phone: +41 (0) 43 322-9800
Phone: +48 (0) 71 734 52-11
Phone: +90 (0) 216- 528 56 56
Phone: +32 (0) 2 7170-933
Phone: +46 (0) 31 7099464
Phone: +86-(0) 21-5489 0202
Phone: +86-(0) 10-8522 1551
Phone: +86-(0) 20-3826 4220
Phone: +86-(0) 23-6773 4988
Phone: +86-(0) 532-8079 1871
Phone: +86-(0) 27-8544 9942
Phone: +65 6563-5533
Phone: +82 (0) 2-523-9726
Phone: +66-2361-3730

marketing.SUS@konicaminolta.com

info.sensing@seu.konicaminolta.eu
info.germany@seu.konicaminolta.eu
info.france@seu.konicaminolta.eu
info.uk@seu.konicaminolta.eu
info.italy@seu.konicaminolta.eu
info.switzerland@seu.konicaminolta.eu
info.poland@seu.konicaminolta.eu
info.sensing@konicaminolta.com.tr
info.benelux@seu.konicaminolta.eu
info.nordic@seu.konicaminolta.eu
hcn_sensing@hcn.konicaminolta.cn
hcn_sensing@hcn.konicaminolta.cn
hcn_sensing@hcn.konicaminolta.cn
hcn_sensing@hcn.konicaminolta.cn
cn_sensing@hcn.konicaminolta.cn
ssg@konicaminolta.sg
sensing-gc@konicaminolta.jp
sensing-gc@konicaminolta.jp



Certificate No: YIA 0937 154
Registration Date:
March 3, 1995



Certificate No: JQA-E-80027
Registration Date:
March 12, 1997



KONICA MINOLTA